MF SERIES
LABORATORY REFRIGERATOR

NULINE
REFRIGERATION

FEATURES

- Top Mounted System
- Cabinet finish in Stainless Steel Interior/Exterior
- Automatic Defrost and Water Disposal
- 5 Adjustable Shelves per Door
- Available in Glass Door (TNG) or Solid Door (TN)
- Digital Display with Built-in Alarms
- Hi/Lo Readout

	2°C to 8°C
	700 L 1400 L
	740w x 830d x 2050h 1480w x 830d x 2050h

+61 3 9562 3355
info@nulinerefrigeration.com.au
7 Longford Court, Springvale VIC 3171
www.nulinerefrigeration.com.au

Distributor
EVOCARE AUSTRALIA PTY LIMITED
A.B.N. 98 078 566 604
Trading as **EVOCARE** and **L&M EQUIPMENT**
P.O. Box 1144, Stafford Qld. 4053
Ph: 07 3355 8000 Fax: 07 3355 5043
Website: http://www.evocare.com.au
Email: sales@evocare.com.au
workshop@evocare.com.au
warehouse@evocare.com.au
accounts@evocare.com.au

Quality Management · ISO 9001
Global-Mark.com.au®

MF SERIES
LABORATORY REFRIGERATOR

NULINE REFRIGERATION

MODEL	MF70TN	MF70TG	MF140TN	MF140TG
Gross Capacity	700 L	700 L	1400 L	1400 L
External Dimensions in mm (w/d/h including castors or legs)	740 x 830 x 2050	740 x 830 x 2050	1480 x 830 x 2050	1480 x 830 x 2050
Internal Dimensions in mm (w/d/h)	600 x 690 x 1475	600 x 690 x 1475	1340 x 690 x 1475	1340 x 690 x 1475
Packed Dimensions in mm (w/d/h including pallet)	760 x 850 x 2100	760 x 850 x 2100	1500 x 850 x 2100	1500 x 850 x 2100
Gross Weight – kg (packed weight)	129	134	215	225
Net Weight – kg	115	120	191	201
Voltage	240V	240V	240V	240V
Temperature Range	2°C to 8°C	2°C to 8°C	2°C to 8°C	2°C to 8°C
Ambient Temperature Range	10°C to 32°C	10°C to 32°C	10°C to 32°C	10°C to 32°C
Refrigerant	R134a	R134a	R134a	R134a
Cooling System / Defrost	Fan Forced	Fan Forced	Fan Forced	Fan Forced
Exterior Cabinet Finish	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Inner Liner Material	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Door	Solid	Heated Glass	Solid	Heated Glass
Door Hinges	RH	RH	LH / RH	LH / RH
Door Handle	Full Length	Full Length	Full Length	Full Length
Type of Controller	Digital	Digital	Digital	Digital
Temperature Display	External	External	External	External
Data Logger	Optional	Optional	Optional	Optional
Door Ajar Alarms	Optional	Optional	Optional	Optional
High and Low Readout	Visual / Audible	Visual / Audible	Visual / Audible	Visual / Audible
Remote Alarm Contacts (BMS Connectivity for Alarms only) (BMS Connectivity for Temperatures)	Optional Optional	Optional Optional	Optional Optional	Optional Optional
Port Entry	Optional	Optional	Optional	Optional
Battery Back Up for Controller	Optional	Optional	Optional	Optional
Power Requirement	10amp GPO	10amp GPO	10amp GPO	10amp GPO
Castors	Yes	Yes	Yes	Yes
Adjustable Shelves	5	5	10	10
Usable Shelf Area in mm (w/d)	530 x 652	530 x 652	530 x 652	530 x 652
Light	LED	LED	LED	LED

Nuline Refrigeration reserves the right to alter the specifications without prior notice.

MF SERIES LABORATORY FREEZER

NULINE REFRIGERATION

FEATURES

- Top Mounted System
- Cabinet finish in Stainless Steel Interior/Exterior
- Automatic Defrost and Water Disposal
- 5 Adjustable Shelves per Door
- Digital Display with Built-in Alarms
- Hi/Lo Readout

	-18°C to -22°C
	700 L 1400 L
	740w x 830d x 2050h 1480w x 830d x 2050h

+61 3 9562 3355
info@nulinerefrigeration.com.au
7 Longford Court, Springvale VIC 3171
www.nulinerefrigeration.com.au

Distributor
EVOCARE AUSTRALIA PTY LIMITED
A.B.N. 98 078 566 604
Trading as **EVOCARE** and **L&M EQUIPMENT**
P.O. Box 1144, Stafford Qld. 4053
Ph: 07 3355 8000 Fax: 07 3355 5043
Website: http://www.evocare.com.au
Email: sales@evocare.com.au
workshop@evocare.com.au
warehouse@evocare.com.au
accounts@evocare.com.au

Quality Management · ISO 9001
Global-Mark.com.au®

MF SERIES LABORATORY FREEZER

NULINE REFRIGERATION

MODEL	MF70BT	MF70BTG	MF140BT	MF140BTG
Gross Capacity	700 L	700 L	1400 L	1400 L
External Dimensions in mm (w/d/h including castors or legs)	740 x 830 x 2050	740 x 830 x 2050	1480 x 830 x 2050	1480 x 830 x 2050
Internal Dimensions in mm (w/d/h)	600 x 690 x 1475	600 x 690 x 1475	761 x 690 x 1475	761 x 690 x 1475
Packed Dimensions in mm (w/d/h including pallet)	761 x 850 x 2100	761 x 850 x 2100	762 x 850 x 2100	762 x 850 x 2100
Gross Weight – kg (packed weight)	138	143	226	255
Net Weight – kg	125	130	202	230
Voltage	240V	240V	240V	240V
Temperature Range	-18°C to -22°C	-18°C to -22°C	-18°C to -22°C	-18°C to -22°C
Ambient Temperature Range	10°C to 32°C	10°C to 32°C	10°C to 32°C	10°C to 32°C
Refrigerant	R404a	R404a	R404a	R404a
Cooling System / Defrost	Fan Forced	Fan Forced	Fan Forced	Fan Forced
Exterior Cabinet Finish	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Inner Liner Material	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Door	Solid	Heated Glass	Solid	Heated Glass
Door Hinge	RH	RH	LH / RH	LH / RH
Door Handle	Full Length	Full Length	Full Length	Full Length
Type of Controller	Digital	Digital	Digital	Digital
Temperature Display	External	External	External	External
Data Logger	Optional	Optional	Optional	Optional
Door Ajar Alarms	Optional	Optional	Optional	Optional
High and Low Readout	Visual / Audible	Visual / Audible	Visual / Audible	Visual / Audible
Remote Alarm Contacts (BMS Connectivity for Alarms only) (BMS Connectivity for Temperatures)	Optional Optional	Optional Optional	Optional Optional	Optional Optional
Port Entry	Optional	Optional	Optional	Optional
Battery Back-Up for Controller	Optional	Optional	Optional	Optional
Power Requirement	10amp GPO	10amp GPO	10amp GPO	10amp GPO
Watts	410W	440W	700W	730W
Castors	Yes	Yes	Yes	Yes
Adjustable Shelves	5	5	10	10
Usable Shelf Area in mm (w/d)	530 x 652	530 x 652	530 x 652	530 x 652

Nuline Refrigeration reserves the right to alter the specifications without prior notice.