

The only safe and accurate method of determining and maintaining saline, irrigation, glycene, parenteral and IPD fluid temperature to the manufacturer's recommendations. Fluid warming cabinets are essential in Maternity, Recovery, Theatre, Specialist and Intensive Care units...

- Stainless Steel Construction with insulation cavity, therefore the exterior is cool to touch
- · Double glazed doors for inventory monitoring
- · Magnetic door closure
- · Special sensor plate for actual fluid temperature monitoring
- Over temperature protection (5°C above setting) and temperature lockout
- Fan-assisted convection heating
- Adjustable shelving; 1 litre and 2 litre bottles and bags can be stored (3 x wire shelves; bottom fixed)
- ARTG Certification 188762 Class I

UNIT DIMENSIONS:	500mm (W) x 595mm (D) x 735mm (H)
VOLTAGE:	240V
CURRENT:	2.8 Amps
PHASE:	Single
HERTZ:	50
SHIPPING WEIGHT:	59 kg
CAPACITY:	Up to 24 x 1 litre bags of fluid; or equivalent
VOLUME:	105 litres
SET TEMPERATURE:	37°C
MAX TEMPERATURE SETTING:	50°C
POWER CONSUMPTION:	Less than 7.8kW/24hrs



WARMING CABINETS (105 LITRE X2)

The Malmet 105 litre x2 Warming cabinets are designed for space-conscious areas of any facility. This cabinet combines the features of Malmet 105 litre Blanket Warming cabinets and Malmet 105 litre Fluid warming cabinets in a variety of combinations to suit your requirements.

- Stainless Steel Construction with insulation cavity, therefore the exterior is cool to touch
- Double glazed doors for inventory monitoring
- Magnetic door closure
- Over temperature protection (5°C above setting) and temperature lockout
- Fan-assisted convection heating
- Adjustable shelving

UNIT DIMENSIONS:	500mm (W) x 595mm (D) x 1380mm (H)	
VOLTAGE:	240V	
CURRENT:	2.8 Amps	
PHASE:	Single	
HERTZ:	50	
SHIPPING WEIGHT:	106 kg	
CAPACITY:	Up to 6 blankets (per blanket cavity) Up to 24 x 1 litre bags of fluid; or equivalent (per fluid cavity)	
VOLUME:	105 litres (per cavity)	
	Blanket Warming Cavity	Fluid Warming Cavity
SET TEMPERATURE:	60°C	37°C
MAX TEMPERATURE SETTING:	60℃	50°C
POWER CONSUMPTION:	Less than 7.8kW/24hrs	



	Product Code	Model No	Description
ABLE MODELS	100-1220	BB105FS	MALMET BLANKET/BLANKET WARMING CABINET (105 LITRE X 2) FREESTANDING WITH FLOOR SKIRT
WAILABLE	100-1221	FF105FS	MALMET FLUID/FLUID WARMING CABINET (105 LITRE X 2) FREESTANDING WITH FLOOR SKIRT
-4	100-1222	FB105FS	MALMET FLUID/BLANKET WARMING CABINET (105 LITRE X 2) FREESTANDING WITH FLOOR SKIRT

MALMET 210 LITRE FLUID WARMING CABINETS

Malmet Fluid Warming cabinets are designed as a safe and accurate method of determining and maintaining saline, irrigation, glycene, parenteral and IPD fluid temperature to the manufacturer's recommendations. Fluid warming cabinets are essential in Maternity, Recovery, Theatre, Specialist and Intensive Care units.

- Stainless Steel Construction with insulation cavity, therefore the exterior is cool to touch
- · Double glazed doors for inventory monitoring
- · Magnetic door closure
- · Special sensor plate for actual fluid temperature monitoring
- Over temperature protection (5°C above setting) and temperature lockout
- Fan-assisted convection heating
- Individual cabinets can be converted to any combination to suit your requirements
- Multi-purpose installation
 Options: Wall/Bench Mounted; Freestanding with Floor Skirt;
 Freestanding on Stand; Freestanding on Castors
- Optional castors (2 fixed; 2 swivel and lockable)
- Adjustable shelving (4 x wire shelves; bottom shelf fixed)
- ARTG Certification 188762 Class I



	F210FS	760mm (W) x 595mm (D) x 995mm (H)
LINUT DIMENSIONS	F210C	760mm (W) x 595mm (D) x 1030mm (H)
UNIT DIMENSIONS:	F210WB	760mm (W) x 595mm (D) x 905mm (H)
	F210S	760mm (W) x 595mm (D) x 1520mm (H)
VOLTAGE:	240V	
CURRENT:	2.8 Amps	
PHASE:	Single	
HERTZ:	50	
SHIPPING WEIGHT:	122 kg	
CAPACITY:	Up to 45 x 1 litre	bags of fluid; or equivalent
VOLUME:	210 litres	
SET TEMPERATURE:	37°C	
MAX TEMPERATURE SETTING:	50°C	
POWER CONSUMPTION:	Less than 7.8kW/	/24hrs



	Product Code	Model No	Description
DELS	100-1140	F210FS	MALMET FLUID WARMING CABINET (210 LITRE) FREESTANDING WITH FLOOR SKIRT
BLEMO	100-1141	F210C	MALMET FLUID WARMING CABINET (210 LITRE) FREESTANDING ON CASTORS
AVAILA	100-1142	F210WB	MALMET FLUID WARMING CABINET (210 LITRE) WALL/BENCH MOUNT
	100-1143	F210S	MALMET FLUID WARMING CABINET (210 LITRE) FREESTANDING ON STAND



WARMING CABINETS 210 LITRE (X2)

Malmet 210 litre Warming cabinets are designed with multi-purpose installation in mind; providing the capabilities of combining the functionality of the Malmet 210 Litre Blanket Warming Cabinet and 210 Litre Fluid Warming Cabinet in a variety of combinations to suit your requirements.

- Stainless Steel Construction with insulation cavity, therefore the exterior is cool to touch
- · Double glazed doors for inventory monitoring
- Magnetic door closure
- Over temperature protection (5°C above setting) and temperature lockout
- Fan-assisted convection heating
- Adjustable shelving

UNIT DIMENSIONS:	All models with Floor Skirt	760mm (W) x 595mm (D) x 1898mm (H)
ONIT DIMENSIONS.	All models on Castors	760mm (W) x 595mm (D) x 1935mm (H)
VOLTAGE:	240V	
CURRENT:	2.8 Amps	
PHASE:	Single	
HERTZ:	50	
SHIPPING WEIGHT:	106 kg	
CAPACITY:	Up to 16 blankets; max 8 blankets/shelf (per blanket cavity) Up to 45×1 litre bags of fluid; or equivalent (per fluid cavity)	
VOLUME:	210 litres (per cavity)	
	Blanket Warming Cavity	Fluid Warming Cavity
SET TEMPERATURE:	60°C	37°C
MAX TEMPERATURE SETTING:	60°C	50°C
POWER CONSUMPTION:	Less than 7.8kW/24hrs	

FREESTANDING WITH FLOOR SKIRT

	KEESTANDING WITH LOOK SKIKI				
	Product Code	Model No	Description		
	100-1240	BB210FS	MALMET BLANKET/BLANKET WARMING CABINET (210 LITRE X2) FREESTANDING WITH FLOOR SKIRT		
MODELS	100-1241	FF210FS	MALMET FLUID/FLUID WARMING CABINET (210 LITRE X2) FREESTANDING WITH FLOOR SKIRT		
AVAILABLE MODELS	100-1242	FB210FS	MALMET FLUID/BLANKET WARMING CABINET (210 LITRE X2) FREESTANDING WITH FLOOR SKIRT		
	100-1243	BS210FS	MALMET BLANKET WARMING/STORAGE CABINET (210 LITRE X2) FREESTANDING WITH FLOOR SKIRT		
	100-1244	FS210FS	MALMET FLUID WARMING/STORAGE CABINET (210 LITRE X2) FREESTANDING WITH FLOOR SKIRT		

FREESTANDING ON CASTORS

	Product Code	Model No	Description
	Product Code	Model No	Description
	100-1250	BB210C	MALMET BLANKET/BLANKET WARMING CABINET (210 LITRE X2) FREESTANDING ON CASTORS
MODELS	100-1251	FF210C	MALMET FLUID/FLUID WARMING CABINET (210 LITRE X2) FREESTANDING ON CASTORS
4VAILABLE	100-1252	FB210C	MALMET FLUID/BLANKET WARMING CABINET (210 LITRE X2) FREESTANDING ON CASTORS
AV4	100-1253	BS210C	MALMET BLANKET WARMING/STORAGE CABINET (210 LITRE X2) FREESTANDING ON CASTORS
	100-1254	FS210C	MALMET FLUID WARMING/STORAGE CABINET (210 LITRE X2) FREESTANDING ON CASTORS





MODEL: FB210C

260 LITRE FLUID WARMING CABINETS

Malmet Fluid Warming cabinets are designed as a safe and accurate method of determining and maintaining saline, irrigation, glycene, parenteral and IPD fluid temperature to the manufacturer's recommendations. Fluid warming cabinets are essential in Maternity, Recovery, Theatre, Specialist and Intensive Care units.



- Stainless Steel Construction with insulation cavity, therefore the exterior is cool to touch
- Double glazed doors for inventory monitoring
- Magnetic door closure
 - Special sensor plate for actual fluid temperature monitoring
 - Over temperature protection (5°C above setting) and
 - temperature lockout
 - Fan-assisted convection heating
 - Individual cabinets can be converted to any combination to suit your requirements
 - Multi-purpose installation
 - Options: Wall/Bench Mounted; Freestanding with Floor Skirt;
 - Freestanding on Stand; Freestanding on Castors
- Optional castors (2 fixed; 2 swivel and lockable)
- Adjustable shelving (4 x wire shelves; bottom shelf fixed)
 - ARTG Certification 188762 Class I



	F260FS	850mm (W) x 595mm (D) x 995mm (H)
UNIT DIMENSIONS:	F260C	850mm (W) x 595mm (D) x 1030mm (H)
ONIT DIMENSIONS:	F260WB	850mm (W) x 595mm (D) x 905mm (H)
	F260S	850mm (W) x 595mm (D) x 1520mm (H)
VOLTAGE:	240V	
CURRENT:	2.8 Amps	
PHASE:	Single	
HERTZ:	50	
SHIPPING WEIGHT:	124 kg	
CAPACITY:	Up to 60 x 1 litre bag	gs of fluid; or equivalent
VOLUME:	260 litres	
SET TEMPERATURE:	37°C	
MAX TEMPERATURE SETTING:	50°C	
POWER CONSUMPTION:	Less than 7.8kW/24l	hrs

	Product Code	Model No	Description
BLE MODELS	100-1160	F260FS	MALMET FLUID WARMING CABINET (260 LITRE) FREESTANDING WITH FLOOR SKIRT
	100-1161	F260C	MALMET FLUID WARMING CABINET (260 LITRE) FREESTANDING ON CASTORS
AVAILA	100-1162	F260WB	MALMET FLUID WARMING CABINET (260 LITRE) WALL/BENCH MOUNT
	100-1163	F260S	MALMET FLUID WARMING CABINET (260 LITRE) FREESTANDING ON STAND

WARMING CABINETS 260 LITRE (X2)

Malmet 260 litre Warming cabinets are designed with multi-purpose installation in mind; providing the capabilities of combining the functionality of the Malmet 260 Litre Blanket Warming Cabinet and 260 Litre Fluid Warming Cabinet in a variety of combinations to suit your requirements.

- Stainless Steel Construction with insulation cavity, therefore the exterior is cool to touch
- Double glazed doors for inventory monitoring
- Magnetic door closure
- · Over temperature protection (5°C above setting) and temperature lockout
- Fan-assisted convection heating
- Adjustable shelving

UNIT DIMENSIONS:	All models with Floor Skirt	850mm (W) x 595mm (D) x 1898mm (H)
ONLI DIMENSIONS:	All models on Castors	850mm (W) x 595mm (D) x 1935mm (H)
VOLTAGE:	240V	
CURRENT:	2.8 Amps	
PHASE:	Single	
HERTZ:	50	
SHIPPING WEIGHT:	106 kg	
CAPACITY:	Up to 18 blankets; max 6 blankets/shelf (per blanket cavity) Up to 60×1 litre bags of fluid; or equivalent (per fluid cavity)	
VOLUME:	260 litres (per cavity)	
	Blanket Warming Cavity	Fluid Warming Cavity
SET TEMPERATURE:	60°C	37°C
MAX TEMPERATURE SETTING:	60°C	50°C
POWER CONSUMPTION:	Less than 7.8kW/24hrs	

FREESTANDING WITH FLOOR SKIRT

Product Code	Model No	Description		
100-1260	BB260FS	MALMET BLANKET/BLANKET WARMING CABINET (260 LITRE X2) FREESTANDING WITH FLOOR SKIRT		
100-1261	FF260FS	MALMET FLUID/FLUID WARMING CABINET (260 LITRE X2) FREESTANDING WITH FLOOR SKIRT		
100-1262	FB260FS	MALMET FLUID/BLANKET WARMING CABINET (260 LITRE X2) FREESTANDING WITH FLOOR SKIRT		
100-1263	BS260FS	MALMET BLANKET WARMING/STORAGE CABINET (260 LITRE X2) FREESTANDING WITH FLOOR SKIRT		
100-1264	FS260FS	MALMET FLUID WARMING/STORAGE CABINET (260 LITRE X2) FREESTANDING WITH FLOOR SKIRT		
	100-1260 100-1261 100-1262 100-1263	100-1260 BB260FS 100-1261 FF260FS 100-1262 FB260FS 100-1263 BS260FS		

FREESTANDING ON CASTORS

	TREESTANDING ON CASTORS								
AVAILABLE MODELS	Product Code	Model No	Description						
	100-1270	BB260C	MALMET BLANKET/BLANKET WARMING CABINET (260 LITRE X2) FREESTANDING ON CASTORS						
	100-1271	FF260C	MALMET FLUID/FLUID WARMING CABINET (260 LITRE X2) FREESTANDING ON CASTORS						
	100-1272	FB260C	MALMET FLUID/BLANKET WARMING CABINET (260 LITRE X2) FREESTANDING ON CASTORS						
	100-1273	BS260C	MALMET BLANKET WARMING/STORAGE CABINET (260 LITRE X2) FREESTANDING ON CASTORS						
	100-1274	FS260C	MALMET FLUID WARMING/STORAGE CABINET (260 LITRE X2) FREESTANDING ON CASTORS						





MODEL: BB260C

420 LITRE FLUID WARMING CABINETS

Malmet Fluid Warming cabinets are designed as a safe and accurate method of determining and maintaining saline, irrigation, glycene, parenteral and IPD fluid temperature to the manufacturer's recommendations. Fluid warming cabinets are essential in Maternity, Recovery, Theatre, Specialist and Intensive Care units.

- · Stainless Steel Construction with insulation cavity, therefore the exterior is cool to touch
- · Double glazed doors for inventory monitoring
- Magnetic door closure
- · Special sensor plate for actual fluid temperature monitoring
- · Over temperature protection (5°C above setting) and temperature lockout
- Fan-assisted convection heating
- Multi-purpose installation
 - Options: Freestanding with Floor Skirt; Freestanding on Castors
- · Optional castors (2 fixed; 2 swivel and lockable)
- · Adjustable shelving (7 x wire shelves; bottom shelf fixed)
- ARTG Certification 188762 Class I

LINUT DIMENSIONS	F420FS	760mm (W) x 595mm (D) x 1585mm (H)	
UNIT DIMENSIONS:	F420C	760 mm (W) x 595mm (D) x 1635mm (H)	
VOLTAGE:	240V		
CURRENT:	2.8 Amps		
PHASE:	Single		
HERTZ:	50		
SHIPPING WEIGHT:	59 kg		
CAPACITY:	Up to 91 x 1 litre bags of fluid; or equivalent		
VOLUME:	420 litres		
SET TEMPERATURE:	37°C		
MAX TEMPERATURE SETTING:	50°C		
POWER CONSUMPTION:	Less than 7.8kW/24hrs		



Queensland Distributor

EVOCARE AUSTRALIA PTY LIMITED

A.B.N. 98 078 566 604
Trading as **EVOCARE** and **L&M EQUIPMENT**P.O. Roy 1144 Stafford Old 4053

Ph W E

P.O. Box 1144, Stafford Qld. 4053
Ph: 07 3355 8000 Fax: 07 3355 5043
Website: http://www.evocare.com.au
Email: sales@evocare.com.au
workshop@evocare.com.au
warehouse@evocare.com.au
accounts@evocare.com.au

AVAILABLE MODELS	Product Code	Model No	Description	
	100-1100	F420FS	MALMET FLUID WARMING CABINET (420 LITRE) FREESTANDING WITH FLOOR SKIRT	
	100-1101	F420C	MALMET FLUID WARMING CABINET (420 LITRE) FREESTANDING ON CASTORS	