

Castors

Elegant futuristic design and leading technology.

Castors from Tente

Evocare stocks a range of **TENTE** castors for institutional patient trolleys, dressing trolleys, beds, shower commodes, etc.

TENTE synthetic institutional castors combine elegant futuristic design and leading technology.

The use of high quality materials and advanced production techniques build the foundation of the outstanding quality provided with this castor.

New technical bearing and locking concepts guarantee smooth motion and ease of operation.

Excellent roll and swivel performance are a trademark of this castor.

Evocare uses high quality synthetic materials for production, which are largely resistant to all known detergents and disinfectants. The compact and smooth surfaced exterior reduces the possibility of picking up dirt and ensures maximum ease of cleaning.

This allows a wide range of applications, such as hospitals and nursing home furniture, medical equipment, serving carts and catering equipment.

Our standard castors in size 100 and 125 mm are available in swivel, rigid, locking design, electrically conductive and washable versions.

Swivel castor			Wheel description		Type				kg (daN)
5320	5328	5327	Wheel diameter	Fitting	mm	mm	mm		
Rigid castor			100	32	77x67	61,5/50x51,5/41,5	141	80	
Total lock castor			125	32	77x67	61,5/50x51,5/41,5	166	100	
5320	5328	5327	PJP 100 P60	100	32	77x67	61,5/50x51,5/41,5	141	80
5320	5328	5327	PJP 125 P60	125	32	77x67	61,5/50x51,5/41,5	166	100
5320	5328	5327	PJP 125 P60-95x70*	125	32	95x70	75x50	166	100
					mm	mm			
5320	5328	5327	PJP 100 R05-18x62*	100	32	18	62	137	80
5320	5328	5327	PJP 125 R05-18x62*	125	32	18	62	162	100
5320		5327	PJP 125 R05	125	32	28	45	162	100
					mm	mm			
5320		5327	PJP 100 S70	100	32	M 10x17		137	80
5320		5327	PJP 125 S70	125	32	M 10x17		162	100

Wheels

PJP

Wheel-center: Polypropylene
Tread: TENTE-prene (Thermoplastic rubber) with integrated threadguards, zinc plated and precision ball bearing.

UAP

Wheel-center: Polyamide
Tread: Polyurethane, with integrated threadguards, yellow chromated and precision ball bearing.

XSP

Wheel-center: Polyamide, electrically conductive
Tread: Polyurethane, electrically conductive with integrated threadguards, yellow chromated, precision ball bearing.

