

Item no.	Type	Max/min length mm	Inner width mm	Outer width max. mm	Width folded max. mm	Max load kg/pair	Weight kg/each
30000-050	Plain ramp	500	182	260	-	350	1,5
30000-105	Plain ramp	1050	182	260	-	350	3,2
30000-130	Plain ramp	1300	182	260	-	350	3,9
30000-155	Plain ramp	1550	182	260	-	350	4,7
30000-200	Plain ramp	2000	182	260	-	350	6,0
30015-100	Telescopic ramp	1000/677	182	279	-	350	4,3
30015-150	Telescopic ramp	1500/927	182	279	-	350	5,7
30015-200	Telescopic ramp	2000/1177	182	279	-	350	7,2
30015-250	Telescopic ramp	2500/1427	182	279	-	200	8,6
30015-300	Telescopic ramp	3000/1677	182	279	-	200	10,1
30020-110	Folding ramp	1100/580	182	260	-	350	4,0
30020-160	Folding ramp	1600/830	182	260	-	350	5,7
30020-210	Folding ramp	2100/1080	182	260	-	350	7,2
30020-260	Folding ramp	2600/1330	182	260	-	200	8,6
30020-310	Folding ramp	3100/1580	182	260	-	200	10,1
30030-100	Wide plain ramp	1000	770	880	-	325	9,7
30030-125	Wide plain ramp	1250	770	880	-	325	12,1
30030-150	Wide plain ramp	1500	770	880	-	325	14,4
30030-200	Wide plain ramp	2000	770	880	-	325	19,1
30030-300	Wide plain ramp	3000	770	880	-	200	28,6
30040-150	Wide folding ramp	1500/780	770	880	-	325	17,5
30040-200	Wide folding ramp	2000/1030	770	880	-	325	22,2
30040-250	Wide folding ramp	2500/1280	770	880	-	200	26,9
30040-300	Wide folding ramp	3000/1530	770	880	-	200	31,7
30070-180	EasyFold Telescopic ramp	1830/1120	760	820	405	325	16,4
30070-210	EasyFold Telescopic ramp	2130/1270	760	820	405	325	18,9
30070-240	EasyFold Telescopic ramp	2440/1430	760	820	405	325	21,4
30070-300	EasyFold Telescopic ramp	3050/1730	760	820	405	200	26,4
30080-095	EasyFold Pro ramp	935	760	776	398	350	7,8
30080-120	EasyFold Pro ramp	1185	760	776	398	350	9,0
30080-150	EasyFold Pro ramp	1485	760	776	398	350	11,4
30080-180	EasyFold Pro ramp	1785	760	776	398	350	13,4
30080-210	EasyFold Pro ramp	2085	760	776	398	350	15,8
30085-165	EasyFold Pro3 ramp	1635	760	786	273	350	13,4

Material

Ramp slopes : Anodised aluminium with skid resistant surface
 End profile and handle : Impact-proof and non-skid plastic
 Brackets : Stainless steel, glass blown
 Brackets 30080 : Plastic

Other measurements

Height of edge : 46 mm
 Height of edge 30080/85 : 40 mm/50 mm
 Angle of contact : max. 12 degrees
 Contact surface
 30000/30015/30020 : 65 mm
 30030/30040 : 110 mm
 30070/30080/30085 : 90 mm

Marking

The product is manufactured in compliance with the Council Directive 93/42/EEC of June 14th 1993, including amendments, as medical device class 1.

Classification

According to ISO 9999 : 18 30 15

30000-xxx & 30030-xxx




30070-xxx




30015-xxx



30080-xxx



30020-xxx & 30040-xxx



30085-xxx

