




HR PHARMACY REFRIGERATOR GLASS DOOR

NULINE
REFRIGERATION

FEATURES

- Fan Forced System
- Door Lock
- Interior Lighting
- Data Logger Included
- Digital Display with Built-in Alarms
- Hi/Lo Readout
- Remote Alarm Contacts



| | |
|---|--|
|  | 2°C to 8°C |
|  | 135 L 350 L 570 L |
|  | 595w x 650d x 830h 595w x 650d x 1850h 775w x 750d x 1850h |



EVOCARE AUSTRALIA PTY LIMITED

A.B.N. 98 078 566 604

Trading as **EVOCARE** and **L&M EQUIPMENT**

P.O. Box 145, Everton Park Qld. 4053

Ph: 07 3355 8000

Website: <http://www.evocare.com.au>

Email: sales@evocare.com.au

workshop@evocare.com.au

warehouse@evocare.com.au

accounts@evocare.com.au



Global-Mark.com.au®

+61 3 9562 3355

info@nuline.au

7 Longford Court, Springvale VIC 3171

www.nulinerefrigeration.com.au

HR PHARMACY REFRIGERATOR GLASS DOOR

| Model | HR200G | HR400G | HR600G |
|--|--------------------------------|--------------------------------|--------------------------------|
| Gross Capacity | 135 L | 350 L | 570 L |
| External Dimensions in mm (w/d/h including castors or legs) | 595 x 650 x 830 | 595 x 650 x 1850 | 775 x 750 x 1850 |
| Internal Dimensions in mm (w/d/h) | 455 x 445 x 665 | 455 x 445 x 1685 | 635 x 545 x 1685 |
| Packed Dimensions in mm (w/d/h including pallet) | 640 x 670 x 1005 | 640 x 670 x 2010 | 830 x 790 x 2010 |
| Gross Weight (packed weight) – kg | 48 | 85 | 102 |
| Net Weight – kg | 45 | 77 | 95 |
| Energy Consumption | 237 kWh/y | 330 kWh/y | 491 kWh/y |
| Voltage | 240V | 240V | 240V |
| Temperature Range | 2°C to 8°C | 2°C to 8°C | 2°C to 8°C |
| Ambient Temperature Range | 10°C to 32°C | 10°C to 32°C | 10°C to 32°C |
| Refrigerant | R600a | R600a | R290 |
| Cooling System / Defrost | Fan Forced / Automatic | Fan Forced / Automatic | Fan Forced / Automatic |
| Exterior Cabinet Finish | Enamelled Steel | Enamelled Steel | Enamelled Steel |
| Inner Liner Material | ABS | ABS | ABS |
| Door | Glass | Glass | Glass |
| Door Hinge | RH | RH | RH |
| Door Handle | Pull Handle | Pull Handle | Pull Handle |
| Type of Controller | Digital | Digital | Digital |
| Temperature Display | External | External | External |
| Data Logger | Included | Included | Included |
| Door Ajar Alarms | Optional | Optional | Optional |
| High and Low Readout | Visual / Audible | Visual / Audible | Visual / Audible |
| Remote Alarm Contacts (BMS Connectivity for Alarms only) (BMS Connectivity for Temperatures) | Yes Optional | Yes Optional | Yes Optional |
| Port Entry | Optional | Optional | Optional |
| Battery Back-Up for Controller | Optional | Optional | Optional |
| Power Requirement | 10amp GPO | 10amp GPO | 10amp GPO |
| Watts | 81W | 178W | 160W |
| Castors | Levelling Legs | Levelling Legs | Levelling Legs |
| Adjustable Shelves | 4 | 7 | 7 |
| Usable Shelf Area in mm (w/d) | 3 x 455 x 405 1 x 438 x 202 | 9 x 455 x 405 1 x 438 x 202 | 9 x 635 x 505 1 x 618 x 302 |
| Light | LED | LED | LED |

HR Pharmacy Refrigerator Solid Door



Features:

- Fan forced system
- Door lock
- Interior lighting
- Data logger included
- Digital display with built in alarms
- Hi / Lo read out
- Remote alarm contact



2°C to 8°C



125 L
350 L
570 L



595w x 650d x 830h
595w x 650d x 1850h
775w x 750d x 1850h

Distributor

EVOCARE AUSTRALIA PTY LIMITED

A.B.N. 98 078 566 604

Trading as **EVOCARE** and **L&M EQUIPMENT**

P.O. Box 1144, Stafford Qld. 4053

Ph: 07 3355 8000 Fax: 07 3355 5043

Website: <http://www.evocare.com.au>

Email: sales@evocare.com.au

workshop@evocare.com.au

warehouse@evocare.com.au

accounts@evocare.com.au



Global-Mark.com.au®

| Model | HR200 | HR400 | HR600 |
|---|--|--|--|
| Gross capacity | 125 L | 350 L | 570 L |
| External dimensions in mm (w / d / h including castors or legs) | 595 x 650 x 830 | 595 x 650 x 1850 | 775 x 750 x 1850 |
| Internal dimensions in mm (w / d / h) | 455 x 445 x 665 | 455 x 445 x 1685 | 635 x 545 x 1685 |
| Packed dimensions in mm (w / d / h including pallet) | 640 x 670 x 1005 | 640 x 670 x 2010 | 830 x 790 x 2010 |
| Gross weight (packed weight) | 48 | 85 | 102 |
| Net weight | 45 | 77 | 95 |
| Energy consumption | 237 kWh/y | 330 kWh/y | 491 kWh/y |
| Voltage | 240v | 240v | 240v |
| Temperature range | 2°C to 8°C | 2°C to 8°C | 2°C to 8°C |
| Ambient temperature range | 10°C to 32°C | 10°C to 32°C | 10°C to 32°C |
| Refrigerant | R600a | R600a | R290 |
| Cooling system / defrost | fan forced | fan forced | fan forced |
| Exterior cabinet finish | enamelled steel | enamelled steel | enamelled steel |
| Inner liner material | ABS | ABS | ABS |
| Door | solid | solid | solid |
| Door hinge | RH | RH | RH |
| Door handle | pull handle | pull handle | pull handle |
| Type of controller | digital | digital | digital |
| Temperature display | external | external | external |
| Data logger | included | included | included |
| Door ajar alarms | optional | optional | optional |
| High and low read out | visual / audible | visual / audible | visual / audible |
| Remote alarm contacts (BMS connectivity for alarms only) | yes | yes | yes |
| (BMS connectivity for temperatures) | optional | optional | optional |
| Port entry | optional | optional | optional |
| Battery back-up for controller | optional | optional | optional |
| Power requirement | 10amp GPO | 10amp GPO | 10amp GPO |
| Watts | 70W | 178W | 115W |
| Castors | levelling legs | levelling legs | levelling legs |
| Adjustable shelves | 4 | 9 | 9 |
| Usable shelf area in mm (w / d) | 2 x large shelf 455 x 405 2 x small shelf 438 x 202 | 8 x large shelf 455 x 405 1 x small shelf 438 x 202 | 8 x large shelf 635 x 505 1 x small shelf 618 x 302 |

Nuline Refrigeration reserves the right to alter the specifications without prior notice.